



Prolab[®] Equipment Labels

The P/TAG label range is made from durable polyester with a special laser print receptive surface. A strong acrylic adhesive ensures long term bonding.

The adhesive is acrylic and designed to give long-term bonding. A smooth, clean, dry metal or plastic surface is required. These labels can be used for a wide range of applications including faceplates, outlets and control panels. They are also suitable for general labelling.

Available in packs of 10 or 100 sheets.

TESTING

| Test | Method |
|----------------------|---|
| Low Temperature | MIL-STD-810F Method 502.4 - 72 hours @ -40°C |
| Elevated Temperature | MIL-STD-202G Method 108A - 2000 hours @ 70°C to 100°C |
| Hydrogen Sulphide | H2S Sour Gas Exposure (2% H2S) |
| UV Weathering* | ISO 4982 Part 3 Method A Cycle 1 - 3000 hours |
| Salt Mist Spray | IEC60068-2-52 Test Kb Salt Mist (Cyclic) |

* Limited external applications generally away from direct sunlight but may be suitable in control boxes etc. Labels generally for internal use such as, control rooms, power stations, substations etc.

TECHNICAL DATA

| | |
|------------------|----------------|
| Printing method: | Standard Laser |
| Material: | Polyester |
| Colours: | White |
| Sheet Size: | A4 |
| RoHS: | Yes |
| Reach: | Yes |



For more information and to discuss your needs please contact our sales team on: +44 (0)1707 373 727 or email sales@silverfox.co.uk | www.silverfox.co.uk | support@silverfox.co.uk

Copyright © Silver Fox | 2019 Version 1



Prolab[®] Equipment Labels

Additional Information

- Print using a standard office laser printer
- Pre-perforated for rapid removal from sheet
- Fits a wide range of applications
- Available in a range of different sizes to suit your needs

ORDER INFORMATION

| Product Code | Label Dims (mm) | Labels Per Sheet | Sheets per Pack | Labels per pack | Colour |
|---------------|-----------------|------------------|-----------------|-----------------|--------|
| P/TAG/1212L* | 12 x 12 | 320 | 10 | 3200 | ○ |
| P/TAG/1438L* | 14 x 38 | 84 | 10 | 840 | ○ |
| P/TAG/1506L* | 15 x 6 | 504 | 10 | 5040 | ○ |
| P/TAG/1512L* | 15 x 12 | 240 | 10 | 2400 | ○ |
| P/TAG/1608L* | 16 x 8 | 360 | 10 | 3600 | ○ |
| P/TAG/1709* | 17 x 9 | 308 | 10 | 3080 | ○ |
| P/TAG/2008* | 20 x 8 | 270 | 10 | 2700 | ○ |
| P/TAG/2207* | 22 x 7 | 288 | 10 | 9200 | ○ |
| P/TAG/2412L* | 24 x 12 | 160 | 10 | 1600 | ○ |
| P/TAG/2610L* | 26 x 10 | 161 | 10 | 1610 | ○ |
| P/TAG/3007L* | 30 x 07 | 210 | 10 | 2100 | ○ |
| P/TAG/3030L* | 30 x 30 | 40 | 10 | 400 | ○ |
| P/TAG/3018L* | 30 x 18 | 65 | 10 | 650 | ○ |
| P/TAG/3012L* | 30 x 12 | 100 | 10 | 1000 | ○ |
| P/TAG/4809L* | 48 x 09 | 112 | 10 | 1120 | ○ |
| P/TAG/5522L* | 55 x 22 | 33 | 10 | 330 | ○ |
| P/TAG/6036L* | 60 x 36 | 21 | 10 | 210 | ○ |
| P/TAG/29730L* | 297 x 30 | 7 | 10 | 70 | ○ |
| P/TAG/A5L* | 210 x 148.5 | 2 | 10 | 20 | ○ |
| P/TAG/A4L* | 297 x 210 | 1 | 10 | 10 | ○ |

* Also available in pack of 100 e.g. P/TAG/1506L(100)

STORAGE INSTRUCTIONS

| | |
|----------------------|---|
| Storage Instructions | Store between 50°F (10°C) and 77°F (25°C) |
| Conditions | Keep in dark conditions |
| Humidity Resistance | 35% to 65% RH |

Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice.



For more information and to discuss your needs please contact our sales team on: +44 (0)1707 373 727 or email sales@silverfox.co.uk | www.silverfox.co.uk | support@silverfox.co.uk

Copyright © Silver Fox | 2019 Version 1