



# Thermal Printer Ribbons

A range of thermal ribbons for the Silver Fox DTP-1/300 'Plug'N'Play thermal printer.

Available in 25mm, 60mm and 110mm lengths, all are 300m long. Coloured ribbons are available for our Fox-Flo® range of cable labels.

## TECHNICAL DATA

Printing method: DTP-1 Printer  
 Standard Ribbon: TSR3  
 Coloured Ribbon: TSR4



Product Type	TSR3/300/25	TSR3/300/60	TSR3/300/110
Legend™ Tie-on LM9013T	N/A	N/A	23,000
Legend™ 2-Part System L6/20T	N/A	N/A	100,000
Legend™ 2-Part System L6/30T	N/A	50,000	50,000
Legend™ 2-Part System L6/50T	N/A	50,000	50,000
Prolab® Wrap-around PSA1/07/2512T	N/A	N/A	30,000
Prolab® Wrap-around PSA1/08/2519T	N/A	N/A	27,200
Prolab® Wrap-around PSA1/08/2524T	N/A	N/A	25,000
Fox-Flo® LSZH Tie-on LCLZ2-5010T	N/A	6,000	6,000
Fox-Flo® LSZH Tie-on LCLZ1-5015T	6,000	6,000	6,000
Fox-Flo® LSZH Tie-on LCLZ3-5015T	N/A	6,000	6,000
Fox-Flo® LSZH Tie-on LCLZ1-5025T	N/A	6,000	6,000
Fox-Flo® LSZH Tie-on LCLZ2-7010T	N/A	4,285	4,285
Fox-Flo® LSZH Tie-on LCLZ1-7015T	4,285	4,285	4,285
Fox-Flo® LSZH Tie-on LCLZ3-7015T	N/A	4,285	4,285
Fox-Flo® LSZH Tie-on LCLZ1-7025T	N/A	4,285	4,285
Fox-Flo® LSZH Tie-on LCLZ1-9015T	3,330	3,330	3,330
Fox-Flo® LSZH Tie-on LCLZ3-9015T	N/A	3,330	3,330
Fox-Flo® LSZH Tie-on LCLZ1-9025T	N/A	3,330	3,330
Fox-Flo® LSZH Tie-on LCLZ1-11015T	2,725	2,725	2,725
Fox-Flo® LSZH Tie-on LCLZ3-11015T	N/A	2,725	2,725
Fox-Flo® LSZH Tie-on LCLZ1-11025T	N/A	2,725	2,725
Fox® Tie-on LCP1-6015T	5,000	5,000	5,000
Fox® Tie-on LCP1-6025T	N/A	5,000	5,000
Fox® Tie-on LCP1-8015T	3,750	3,750	3,750
Fox® Tie-on LCP1-8025T	N/A	3,750	3,750
Fox® Tie-on LCP1-10015T	3,000	3,000	3,000
Fox® Tie-on LCP1-10025T	N/A	3,000	3,000
Endurance® Valve Tags EVTP1-6050T	N/A	5,000	5,000
Endurance® Valve Tags EVTP1-8050T	N/A	3,750	3,750
Prolab® Asset Label P/AT01/5025T	N/A	N/A	24,000
Prolab® Asset Label P/AT01/6010T	N/A	N/A	50,000
Prolab® Raised Profile P/RPL01/5025T	N/A	8,100	8,100



For more information and to discuss your needs please contact our sales team on: +44 (0)1707 373 727 or email [sales@silverfox.co.uk](mailto:sales@silverfox.co.uk) | [www.silverfox.co.uk](http://www.silverfox.co.uk) | [support@silverfox.co.uk](mailto:support@silverfox.co.uk)



# Thermal Printer Ribbons

Product Type	TSR3/300/60	TSR3/300/60	TSR3/300/110	TSR3/300/110
	1 Reel	2 Reels	1 Reel	2 Reels
Legend™ Non-Shrink 10mm Lengths	30,000	60,000	30,000	60,000
Legend™ Non-Shrink 25mm Lengths	12,000	24,000	12,000	24,000
Legend™ Non-Shrink 50mm Lengths	6,000	12,000	6,000	12,000
Legend™ Non-Shrink 75mm Lengths	4,000	8,000	4,000	8,000
Legend™ Non-Shrink 100mm Lengths	3,000	6,000	3,000	6,000

Product Type	TSR3/300/60	TSR3/300/60	TSR3/300/110	TSR3/300/110
	1 Reel	2 Reels	1 Reel	2 Reels
Legend™ Heat-Shrink 10mm Lengths	30,000	60,000	30,000	60,000
Legend™ Heat-Shrink 25mm Lengths	12,000	24,000	12,000	24,000
Legend™ Heat-Shrink 50mm Lengths	6,000	12,000	6,000	12,000
Legend™ Heat-Shrink 75mm Lengths	4,000	8,000	4,000	8,000
Legend™ Heat-Shrink 100mm Lengths	3,000	6,000	3,000	6,000

Product Type	TSR3/300/60	TSR3/300/60
	1 Reel	2 Reels
Legend™ LSZH Heat-Shrink 10mm Lengths	30,000	60,000
Legend™ LSZH Heat-Shrink 25mm Lengths	12,000	24,000
Legend™ LSZH Heat-Shrink 50mm Lengths	6,000	12,000
Legend™ LSZH Heat-Shrink 75mm Lengths	4,000	8,000
Legend™ LSZH Heat-Shrink 100mm Lengths	3,000	6,000



For more information and to discuss your needs please contact our sales team on: +44 (0)1707 373 727 or email [sales@silverfox.co.uk](mailto:sales@silverfox.co.uk) | [www.silverfox.co.uk](http://www.silverfox.co.uk) | [support@silverfox.co.uk](mailto:support@silverfox.co.uk)



# Thermal Printer Ribbons

Product Code	Application	Width (mm)	Length (m)	Rolls / Pack	Colours
TSR3/300/25	Fox-Flo® & Fox® < 15mm	25	30	2 Rolls	●
TSR3/300/60	All Applications	60	30	1 Roll	●
TSR3/300/110	All Applications	110	30	1 Roll	●
TSR4/300/60*	Fox-Flo® Labels	60	30	1 Roll	○ ● ● ●

\*Specify colour when ordering



## STORAGE INSTRUCTIONS

Storage Instructions	Store between 50°F (10°C) and 77°F (25°C)
Conditions	Keep in dark conditions
Humidity Resistance	20% to 80% RH

Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice.



For more information and to discuss your needs please contact our sales team on: +44 (0)1707 373 727 or email [sales@silverfox.co.uk](mailto:sales@silverfox.co.uk) | [www.silverfox.co.uk](http://www.silverfox.co.uk) | [support@silverfox.co.uk](mailto:support@silverfox.co.uk)

Copyright © Silver Fox | 2019 Version 1